SEFSC INSPECTION CHECKLIST

The following checklist is a guide. It may be used in its entirety or be modified to the specific user's needs by adding or subtracting items from the checklist. For questions concerning any item, contact the SEFSC SECO.

ABRASIVE WHEEL EQUIPMENT GRINDERS

Name:		Date :	
Location of Inspection:			
1. Is the work rest used and kept adjusted to within 1/8 inch of the wheel?	Yes 🗆 No 🗀	Comments:	
2. Is the adjustable tongue on the topside of the grinder used and kept adjusted to within 1/4 inch of the wheel?	Yes 🗆 No 🗆	Comments:	
3. Do side guards cover the spindle, nut, and flange and 75 percent of the wheel diameter?	Yes 🗆 No 🗆	Comments:	
4. Are bench and pedestal grinders permanently mounted?	Yes 🗆 No 🗆	Comments:	
5. Are goggles or face shields always worn when grinding?	Yes 🗆 No 🗆	Comments:	
6. Is the maximum RPM rating of each abrasive wheel compatible with the RPM rating of the grinder motor?	Yes 🗆 No 🗆	Comments:	
7. Are fixed or permanently mounted grinders connected to their electrical supply system with metallic conduit or other permanent wiring method?	Yes 🗆 No 🗆	Comments:	
8. Does each grinder have an individual on and off control switch?	Yes 🗆 No 🗆	Comments:	

9. Is each electrically operated grinder effectively grounded?	Yes 🗆 No 🗆	Comments:
10. Before new abrasive wheels are mounted, are they visually inspected and ring tested?	Yes 🗆 No 🗆	Comments:
11. Are dust collectors and powered exhausts provided on grinders used in operations that produce large amounts of dust?	Yes 🗆 No 🗆	Comments:
12. Are splashguards mounted on grinders that use coolant, to prevent the coolant from reaching employees?	Yes 🗆 No 🗆	Comments:
13. Is cleanliness maintained around grinder?	Yes 🗆 No 🗆	Comments: